


# GIUNTI UNIVERSALI

## RANGER COUPLINGS

### COR



DN	DE tubo Pipe OD	A mm	H mm	Tiranti - Bolts qtà/qty	L
DN50	46-76	180	100	4	M12x180
DN65	63-85	180	100	4	M12x180
DN80	86-104	190	100	4	M12x180
DN100	109-128	214	100	4	M12x180
DN125	138-153	250	100	4	M12x180
DN150	159-182	278	105	4	M12x200
DN175	192-210	300	130	4	M12x220
DN200	218-235	324	130	4	M12x220
DN225	235-252	360	130	6	M12x230
DN250	242-268	406	130	6	M12x230
DN250	266-297	406	130	6	M12x230
DN300	315-332	440	130	6	M12x230
DN300	322-340	452	130	6	M12x230
DN350	351-378	510	165	8	M16x270
DN350	374-391	510	165	8	M16x270
DN400	386-415	540	165	8	M16x270
DN400	400-429	560	165	8	M16x270
DN450	480-500	630	165	10	M16x270
DN500	500-535	700	165	10	M16x270
DN600	600-635	830	165	10	M16x270
DN700	710-745	960	165	12	M16x310

<b>CORPO</b>	Acciaio secondo EN10025 grado S275 / ASTM A283 o ghisa sferoidale GGG50
<b>CONTROFLANGIA</b>	Ghisa sferoidale ASTM A536 65-45-12 / GGG50 / BS2789 420
<b>GUARNIZIONI</b>	EPDM per acqua potabile (NBR su richiesta)
<b>TIRANTI</b>	Acciaio Zincato - Bulloni secondo DIN 603 Grado 8.8, protetti con tappo in plastica. Dado secondo DIN934 e rondella secondo DIN125. Tiranti in acciaio inossidabile su richiesta
<b>RIVESTIMENTO</b>	Vernice epossidica, min. 250 micron
<b>PRESSIONE DI ESERCIZIO</b>	PN16

<b>BODY</b>	Steel according to EN10025 grade S275 / ASTM A283 or ductile iron GGG50
<b>END RING</b>	Ductile Iron ASTM A536 65-45-12 / GGG50 / BS2789 420
<b>GASKETS</b>	EPDM for potable water (NBR on request)
<b>BOLTS</b>	Galvanized Steel - Bolts DIN 603 Grade 8.8, protected with plastic cap. According to DIN934 nut and washer according to DIN125. Tie rods in stainless steel on request
<b>COATING</b>	Epoxy coating, min. 250 micron
<b>OPERATING PRESSURE</b>	PN16