

# P374

## Intrinsically Safe Color Video Inspection System

The Mini Flexiprobe system sets new standards by offering an intrinsically safe solution that allows successful inspection and reporting within Zone 0 environments



**FEATURES  
/BENEFITS**

- 25mm (1") to 100mm (4") Pipe Inspections
- 61 Meters (200 ft) of semi rigid rod
- Intrinsically safe system certified to EE x ia IIC T6 for Zone 0 Hazardous environments
- True portability, weighs only 21kg (46lbs) and operates from a 12V DC external supply
- Composite video output/input allowing connection to a video recorder or external monitor
- Integrated high resolution 6.4" Color LCD allowing improved image recognition, retractable sun visor built in reducing the effects of sunlight on the screen
- QWERTY Keyboard for text annotation on site, with 9 pages of user defined text available, 9 programmable user defined fields enabling faster text generation
- A truly waterproof system for operation in most weather conditions, protected to Environmental spec IP55
- CMOS camera technology allowing increased operating time through low power consumption
- Maintenance free, White LED's for increased performance and reliability
- Integral electronic meterage counter that displays distance on screen in 0.1m increments which is accurate to +/- 1%



# P374



12V DC Lead



Camera



3" Skids



4" Radial Skids



4" Axial Skids



## Technical Specifications




### CAMERA & LIGHthead

- **Diameter**
  - 24mm (0.94")
- **Full Diameter Length**
  - 17mm (0.67")
- **Total length**
  - 31mm (1.22")
- **Material**
  - 300 Series Stainless Steel and Epoxy Resin Potted Lighthead
- **Focal Length**
  - 6.35mm (0.25") to infinity, manually adjustable
- **Power consumption**
  - 100mA
- **Sensor Transfer Type**
  - CMOS
- **Active Pixel Matrix**
  - 510 x 492
- **Horizontal resolution**
  - 360TVL per picture height
- **Sensitivity**
  - 3 lux
- **Viewing angle**
  - 44°
- **Voltage**
  - 21v max
- **Waterproofing**
  - IP68 11Bar (160psi)

### CONTROL UNIT & COILER

- **Weight**
  - 46lbs (21kg)
- **Voltage**
  - Auto Sensing 110v - 240v or 12v DC
- **Consumption Unit**
  - 3w
- **Waterproofing**
  - IP55
- **Video output**
  - Composite
- **Video input**
  - Composite
- **Height**
  - 900mm (35.4")
- **Width**
  - 600mm (23.6")
- **Depth**
  - 300mm (12")
- **Approvals**
  - CE and FCC compliant

EEx ia IIC T6

FM Class: 3600, 3610, 3810  
 P374 Camera: IS/1/1/ABCD/T6  
 Cage Assy. Coiler: AIS/1/1/ABCD

## America

### Radiodetection

154 Portland Road  
Bridgton, ME 04009, USA  
Tel: +1 (207) 647 9495  
Toll Free: +1 (877) 247 3797  
Fax: +1 (207) 647 9496  
Email: [rd.sales.us@spx.com](mailto:rd.sales.us@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)

### Pearpoint

39-740 Garand Lane, Unit B  
Palm Desert, CA 92211, USA  
Tel: +1 800 688 8094  
Tel: +1 760 343 7350  
Fax: +1 760 343 7351  
Email: [pearpoint.sales.us@spx.com](mailto:pearpoint.sales.us@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)

### Radiodetection (Canada)

344 Edgeley Boulevard, Unit 34  
Concord, Ontario L4K 4B7, Canada  
Tel: +1 (905) 660 9995  
Toll Free: +1 (800) 665 7953  
Fax: +1 (905) 660 9579  
Email: [rd.sales.ca@spx.com](mailto:rd.sales.ca@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)

## Europe

### Radiodetection Ltd (UK)

Western Drive  
Bristol BS14 0AF, UK  
Tel: +44 (0) 117 976 7776  
Fax: +44 (0) 117 976 7775  
Email: [rd.sales.uk@spx.com](mailto:rd.sales.uk@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)

### Radiodetection (France)

13 Grande Rue, 76220  
Neuf Marché, France  
Tel: +33 (0) 2 32 89 93 60  
Fax: +33 (0) 2 35 90 95 58  
Email: [rd.sales.fr@spx.com](mailto:rd.sales.fr@spx.com)  
Web: <http://fr.radiodetection.com>

### Radiodetection (Benelux)

Industriestraat 11  
7041 GD 's-Heerenberg, Netherlands  
Tel: +31 (0) 314 66 47 00  
Fax: +31 (0) 314 66 41 30  
Email: [rd.sales.nl@spx.com](mailto:rd.sales.nl@spx.com)  
Web: <http://nl.radiodetection.com>

### Radiodetection (Germany)

Groendahlscher Weg 118  
46446 Emmerich am Rhein, Germany  
Tel: +49 (0) 28 51 92 37 20  
Fax: +49 (0) 28 51 92 37 520  
Email: [rd.sales.de@spx.com](mailto:rd.sales.de@spx.com)  
Web: <http://de.radiodetection.com>

## Asia-Pacific

### Radiodetection (Asia-Pacific)

Room 708, CC Wu Building  
302-308 Hennessy Road, Wan Chai  
Hong Kong SAR, China  
Tel: +852 2110 8160  
Fax: +852 2110 9681  
Email: [rd.sales.cn@spx.com](mailto:rd.sales.cn@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)

### Radiodetection (China)

Hongfu Mansion, Room 61622  
Zheng Ge Zhuang, Bei Qi Jia Town  
Chang Ping District  
Beijing 102209, China  
Tel: +86 (0) 10 8975 5540  
Fax: +86 (0) 10 8975 5640  
Email: [rd.service.cn@spx.com](mailto:rd.service.cn@spx.com)  
Web: <http://cn.radiodetection.com>

### Radiodetection (Australia)

Unit H1, 101 Rookwood Road,  
Yagoona NSW 2199, Australia  
Tel: +61 (0) 2 9707 3222  
Fax: +61 (0) 2 9707 3788  
Email: [rd.sales.au@spx.com](mailto:rd.sales.au@spx.com)  
Web: [www.radiodetection.com](http://www.radiodetection.com)



To see the full range of products and services provided by Radiodetection visit: [www.radiodetection.com](http://www.radiodetection.com)

©2011 Pearpoint Ltd. / Radiodetection Ltd. – SPX Corporation. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. SPX, Radiodetection and flexiprobe are trademarks of Radiodetection Ltd. and SPX Corporation. Windows XP, Windows Vista and Windows 7 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.

